





仕 様		
標準使用状態	周囲温度	-20～55℃
	相対湿度	45～85%
	標高	2000 m以下
保護構造の種類	IP00〔65(防噴流形) 防油形〕	
定格	定格絶縁電圧	600 V
	定格使用電圧	下表参照
	定格通電電流	10A
	定格使用電流	下表参照
等級	閉路及び遮断電流容量による級別	AC-15級
	開閉頻度による号別	0号(1800回/時)
	機械的及び電氣的開閉耐久性による種別	- 種(50万回)
性能	操作部強度	250N 1分間
	端子部強度	0.8N・m 15秒間
	操作力	約12N(接点構成1a,1b)
	温度上昇	40K以下
	絶縁抵抗	500 V 100MΩ以上
	耐電圧	AC2200 V 1分間
	接触抵抗	30mΩ以下
	耐衝撃性	500/100m/s <sup>2</sup>
	耐振動性	15m/s <sup>2</sup>
	耐湿性	40℃ 93% 96時間
	耐寒性	-40℃ 72時間
	耐熱性	70℃ 16時間
	最小使用電流	DC5V-5mA




## 取付穴の寸法



送記

1. 図はHC形コブカ1212(接続構成 11:1α1b)付とする。
2. 厚さ 1.5mm2枚、3mm1枚
3. ( )内は色記号
4. カバネット専用1212(1212内部の軸の色が水色)ただし、コブカ1212には基本形式HC-Aのみ表示。
5. コブカ1212の積重ね段数で異なる。  
コブカ1212の積重ねは最大2段

## 形式名の呼び方



10:1a
01:1b
20:2a
02:2b
11:1a1b
30:3a
03:3b
40:4a
04:4b
22:2a2b


	AC-15級	DC-13級	DC-12級
24V	10A	6A	6A
48V	10A	2A	3A
110V	6A	0.7A	2A
220V	4A	0.3A	1A
440V	1.5A	-	-

ITEM	DESCRIPTION	MATERIAL	FINISH	QTY	NOTE

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN MILLIMETER  
TOLERANCES ON

DRAWING NO. A-71701A51

DIMENSIONS ± — PROJECTION IS TRIGONOMETRY DO NOT SCALE DRAWING	ANGLES ±	A22PTEH % %
--	----------	-------------

		PROJECTION IS THIRD ANGLE DO NOT SCALE DRAWING	ACCEPTED
見直し	APR.18 2012 M.K	DRAWN MKITAHARA APR.18 2012	SCALE 1/1
DESCRIPTION	CHECKED DATE	APPROVED JARUGA APR.18 2012	 Jaruga